

MODEL RB50A

HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



SUPPLIED WITH UNIT

Charger

Output Cable

	RB 50A
Max amps	1500 (Nom. short circut current) 2300 (Max. short circuit current)
Capacity	27 Amp Hrs @ 10 hr rate
Max Voltage	26V DC
Size (cm)	L 35 x W 10 x H 38
Weight kg	23
Operating Temp.	-40°C - +60°C
Case	Stainless steel
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	2m heavy duty cable with aircraft connector
Charger	8 A Electronic universal AC input. Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

OPTIONAL EXTRAS

Thermal Protection Bag

Various output cable lengths

Croc Clips

Various Connectors

Ramp Trolley

25A, 50A, 75A or 100A 28V DC power supply

- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · Works in any orientation.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- · Starts piston, turbine and turbo propaircraft and helicopters
- · Lightweight portable start power at remote locations.
- · External charger for prolonged unit life.