

## MODEL **TWIN RB**50A HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



SUPPLIED WITH UNIT	
2 x Charger	
Output Cable	
Parallel Joining Cable	
Twin Trolley	
2 x Thermal Protection Bag	

<b>OPTIONAL EXTRAS</b>	
Various output cable lengths	
Croc Clips	
Various Connectors	
25A, 50A, 75A or 100A 28V DC power supply	

	TWIN RB50A
Max amps	3000 (Nom. short circut current) 4600 (Max. short circuit current)
Capacity	58 Amp Hrs @ 10 hr rate
Max Voltage	26V DC
Size (cm)	2 X L 35 x W 10 x H 38
Weight kg	58
Operating Temp.	-40°C - +60°C
Case	Stainless steel
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	2m heavy duty cable with aircraft connector
Charger	2 X 8 A Electronic universal AC input. Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- Tough and compact.
- $\cdot$  No memory effect.
- Works in any orientation.
- High charge retention.
- · Long shelf life.
- Fast recharge.
- External charger for prolonged unit life.
- $\cdot$  No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- Starts Main Battle Tanks.
- Starts Armoured Fighting Vehicles.
- Lightweight portable start power at remote locations.

www.redboxint.com sales@redboxint.com Tel +44 (0) 1794 518888 Fax +44 (0) 1794 518848