

MODEL **TC**3000/100-4

HIGH POWER, MULTIPLE START AND CONTINUOUS DC POWER UNIT (NSN 6130-99-753-1103)

Max amps



SUPPLIED WITH UNIT

Output Cable

OPTIONAL EXTRAS

Towbar

Handlebar and Casters

Various Output Cable Lengths

Various Connectors

Capacity 76 Amp Hrs @ 10 Hr rate **Max Start Voltage 26V DC** 28.5v DC Continuous voltage **Continuous power** 100 amps 95v - 270v **AC input** Size (cm) L89 W78 H46 125 Weight nom kg **Operating Temp** -40°C - + 50° C Zinc Coated Steel Case **Voltage indication** LED display **Performance** LED display monitoring **Output Cable** 3m heavy duty cable with aircraft connector Charger 100A Electronic inbuilt. Charging time less than 1 hour from 50%. **Plug Selector** UK 240V 16A USA 220V 20A or 30A **Other Countries** Please state country when ordering

TC3000/100-4
3500 (Nom. short circut current)

5200 (Max. short circuit current)

PROTECTION

- Overload.
- Over Voltage.



Specification may change without notice

- · Weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Continuous 28V DC power supply
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- · Portable start power at remote locations.

www.redboxint.com sales@redboxint.com Tel +44 (0) 1794 518888 Fax +44 (0) 1794 518848